

## INFORMATION TO BE PROVIDED BY MANUFACTURERS

### 3.1 Servers

Product name : SX-Aurora TSUBASA A311-8

<b>a</b>	<b>product type</b>	HPC server		
<b>b</b>	<b>manufacturer's name, registered trade name and registered trade address at which they can be contacted;</b>	NEC 5-7-1,Shiba,Minato-ku,Tokyo,Japan		
<b>c</b>	<b>product model number</b>	VSA411		
		Low-end performance configuration	High-end performance configuration	
		VSA411	VSA411	
<b>d</b>	<b>year of manufacture</b>	2020		
<b>e</b>	<b>PSU efficiency</b>	Single output	Single output	
	<b>Power Supply Type</b> <b>PSU Efficiency at 10 % , 20 % , 50 % and 100 % of Loadings</b>	92.2%@10% 95.1%@20% 96.1%@50% 94.4%@100%	92.2%@10% 95.1%@20% 96.1%@50% 94.4%@100%	
<b>f</b>	<b>PSU power factor at 50 % of the rated load level</b>	1.000@50%	1.000@50%	
<b>g</b>	<b>PSU rated power output (W)</b>	2000	2000	
<b>h</b>	<b>idle state power(W)</b>	614.4	718.5	
<b>i</b>	<b>list of all components for additional idle power allowances</b>	<b>additional PSU</b>	3	3
		<b>HDDs or SSDs</b>	2	2
		<b>additional memory</b>	92	188
		<b>additional buffered DDR channels</b>	0	0
		<b>additional I/O devices</b>	Model: Intel C622 Dual Port 10GBase-T Type: Ethernet Num. Ports : 2 Link Speed: 10(Gbps)	Model: Intel C622 Dual Port 10GBase-T Type: Ethernet Num. Ports : 2 Link Speed: 10(Gbps)
<b>j</b>	<b>maximum power(W)</b>	722.3	924.3	
<b>k</b>	<b>declared operating condition class</b>	A1	A1	
<b>l</b>	<b>idle state power (Watts) at the higher boundary temperature of the declared operating condition class</b>	691.2	795.3	
<b>m</b>	<b>the active state efficiency and the performance in active state of the server</b>	6.5	9.6	
<b>n</b>	<b>information on the secure data deletion functionality</b>	Linux Standard Command ( shred or dd)		
<b>o</b>	<b>for blade servers, a list of recommended combinations with compatible chassis</b>	-		
<b>p</b>	<b>a list of all model configurations</b>	<b>Processors</b>	Intel Xeon Silver 4208, Intel Xeon Gold 6226	
		<b>Memory Type</b>	DDR4-2933	
		<b>Storage</b>	SSD 960GB	